



S Series

SVL65-2SH

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

FEATURES

Vertical Lift Path Loader Frame  
 Standard Front Quick Coupler, Float Standard  
 Loader Arm Self-Leveling with on/off switch  
 Loader Boom Lock  
 Adjustable, Vinyl, Suspension Seat  
 2" Retractable Seat Belt and 2-Piece Seat Bar  
 12V Electric Outlet  
 17.4 gpm Auxiliary Hydraulics standard, 27 gpm Option  
 Direct To Tank Return Line  
 Rigid Mounted Undercarriage, 4 Lower Track Rollers  
 Two Speed Travel System  
 Automatic Wet Disk Parking Brake  
 Kubota 4 Hydraulic Pump Load Sensing System  
 Hydraulic Joystick Controls, Optional Multi-Function Grips  
 ISO Operating Pattern  
 Hand And Foot Throttle Controls  
 Electronic Travel Torque Management  
 Automatic Glow Plugs  
 Key Switch Stop System  
 Self Bleed Fuel System  
 2 Front and 2 Rear Working Lights  
 Hour Meter, Engine Temperature and Fuel  
 Gauges and Warning Lights  
 Horn and Backup Alarm  
 Lockable Fuel Cap  
 Bolt On Grab Handles to enter machine

CONFIGURATION

**Cab:** Open ROPS/FOPS  
**Tracks:** 12.6" Rubber Tracks  
**Coupler:** Hydraulic Quick Coupler

ENGINE

V2607-CE-TE4 Tier 4 Final Diesel Engine  
 4 Cylinder, 4 Cycle, Turbo Charged  
 68 Gross HP @ 2400 rpm (SAE J1995)

DIMENSIONS

Cab Height 79.9"  
 Width (without attachment) 65.2"  
 Width with wide track option (without attachment) 67.7"  
 Length (without attachment) 107.6"  
 Length of Track on Ground 57.9"

OPERATIONAL DIMENSIONS

Operating Weight\*, SVL65-2SH 8,105 lbs.  
 Rated Operating Capacity (@ 35% of Tipping Load) 2,100 lbs.  
 Rated Operating Capacity (ROC) @ 50% of Tipping Load 3,000 lbs.  
 Tipping Load 6,000 lbs.  
 Auxiliary Hydraulics Flow 17.4 gpm  
 Travel Speed (Low / High) 4.9 / 7.1 mph  
 Reach @ Maximum Height 34.9"  
 Height to Hinge Pin 118.5"  
 Ground Pressure (Standard Track) 5.0 psi  
 Ground Pressure (Wide Track) 4.2 psi

\* Includes operator's weight, 165 lbs.